



Embroidered Felt Emblems [ECE-FE]

Technical Specifications
rev. 2011-03a

Product Details

Emblem Dimensions:

- **Minimum** emblem size is 1" x 1" (2.54cm x 2.54cm) – without merrow border.
- **Minimum** emblem size is 1" x 2" (2.54cm x 5.08cm) – with merrow border.
- **Maximum** emblem size is 12" x 12" (30.48cm x 30.48cm).

Design Lettering Dimensions:

The text within a design should not be less than 4mm (0.16") in height. Smaller text may need to be altered to embroider slightly larger. For designs requiring a lot of small text, Woven Emblems or printed emblems may be a viable alternative.



Fabric Type & Colours:

100% polyester felt fiber. 76+ colours to choose from.

The fabric content is 100% polyester felt fiber (1.1mm thick – 210g per square yard) constructed for embroidery purposes. Choose from 76 standard colours, which can be found on the [Emblemtex Embroidered Felt Emblem Fabric Chart](#).

Thread Type & Colours:

100% polyester. 120+ colours to choose from. 15 colours per design maximum.

Emblemtex uses 100% polyester Madeira Polyneon™ thread. Choose from over 120 standard colours, which can be found on the [Emblemtex Embroidered Emblem Thread Chart](#). A maximum of 15 thread colours can be chosen per design. Extra charges are applicable when using metallic or glow-in-the-dark threads.

Backing Types:

4 options. Low-melt glue • Velcro® • pressure sensitive "stick-on" • non-woven material (no-glue)

Border / Edge Styles:

3 options. Merrowed border • stitched border • no border


Custom Embroidered Felt Emblems can be manufactured with merrowed borders, a separately stitched over-lock edge. The ability to sew a merrowed border onto an emblem is directly related to the emblem shape. Odd, intricate shapes may not be suitable for merrow application. Choose one colour of thread for the merrowed border from the [Emblemtex Embroidered Emblem Thread Chart](#).



Merrow Border Limitations:


As noted above, Custom Embroidered Felt Emblems can be manufactured with merrowed borders. The edges of the emblem are guided through a surging, over-lock sewing machine by hand, and a heavy stitching is applied. Shapes with edges that are completely open and “exterior” are more easily merrowed. However, odd, intricate shapes with edges that angle back towards the interior of the emblem, generally cannot be merrowed.

Shapes that can be merrowed.



Shapes that cannot be merrowed.

Images are not to size.



Design / Emblem Treatment Options:

Custom Embroidered Felt Emblems can be produced with **3D-puff** embroidery stitching to provide another element of texture and dimension. Emblems can also be configured as **double-sided** to create key-chains or pull-tags. Depending on the shape, double-sided emblems can be created in different formats such as:

- The same design on both sides.
- The same design on both sides, but using different colours.
- Two completely different designs on both sides.
- A design on one side and “blank” emblem fabric on the reverse side.




Images shown are to illustrate design treatment, not emblem type.

Accessory Attachment Options:

Custom Embroidered Felt Emblems can be manufactured with a range of attachment options based on the following list.

Button Loop¹ • Butterfly Clutch Pin² • Push-Button-Snap³ • Fabric Loop & Split-Ring⁴ • Button Slit⁵ • Grommet & Split-Ring⁶ • Grommet & Chain⁷ • Plastic Strap & Plastic Sleeve (luggage)⁸ • Plastic Strap (luggage)⁹ • Half-Moon Clip (as pull-tag)¹⁰ • Grommet & Split-Ring (as pull-tag)¹¹ • Grommet & Swivel Split-Ring (as pull tag)¹² • Grommet & Split-Ring Coupling¹³ • Grommet & Swivel Clasp Hook¹⁴ • Grommet & Swivel Snap-Hook¹⁵ • Ornament String (gold)¹⁶ • Grommet¹⁷ • Bar Pin with Catch¹⁸



Images shown are to illustrate accessories, not emblem type.

Application & Wash Guidelines

Application Methods:

Sew-on, heat seal or stick-on. The manner in which embroidered emblems can be attached to garments or other textile products relates directly to the type of backing used in the manufacturing process, the size of the emblems and the types of materials that the emblems will be attached to. Almost all emblems can be sewn on, and when it comes to heat seal application, smaller emblems are easier to work with. The chart below outlines the application options relative to backing types.

backing type	sew on application	hand application	hand iron application	heat seal application	temperature	pressure	cycle time
low-melt glue	yes	no	no	yes	365°F to 385°F (185°C to 196°C)	80 PSI *	15 to 20 seconds
Velcro®	no	yes	no	no	* These recommended settings are based on manually operated or air operated heat seal machines with top iron heat only.		
pressure sensitive “stick-on”	possible	yes	no	no			
non-woven material (no glue)	yes	no	no	no			

Heat Seal Notes & Tips:

- Emblems should be heat sealed to the garment using a complete cycle time on both the front side and the back side of the garment and emblem. Emblems with heavier embroidery may require longer heat seal application cycle times beyond the ranges noted above.
- **Thicker fabrics** may require longer cycle times beyond the ranges noted above.
- **Covering the emblem** with a sheet of Teflon® or paper towel prior to the heat seal cycle may help to reduce a “crushing” affect, and may help to protect the garment from scorching.
- **White materials** (knits or blends) may scorch if heat seal temperatures are too high. It is recommended that fabrics be tested first.
- **Pique knit and fleece** materials may be sensitive to heat and pressure, with the possibility of being crushed.
- **Rib-knit and stretch fabrics** may pucker or distort when emblems are heat sealed to them. It is recommended that these fabrics be tested first. For items such as toques and scarves, it is recommended to have emblems sewn on rather than heat sealed.
- **Terry knit materials** such as towels and bathrobes may not provide a smooth enough surface for proper heat seal application. It is recommended that emblems be sewn on to these types of products.
- **Treated fabrics** finished with coatings, sizing or repellants may not allow for proper heat seal bonding.
- Items made with leather, suede, nylon, synthetics, nylon-shell, interlinings, rubberized coatings and reflective fabrics, such as jackets and luggage, may react poorly to heat seal temperatures depending on thickness, weave, texture and weight. It is recommended that these fabrics be tested first, with possible heat seal time and temperature adjustments. In many cases, it may be better to have emblems sewn on to these materials.
- **Caps** can sometimes be difficult to work with for heat seal applications. To achieve a higher potential for heat seal application success on caps, it is recommended that emblems not be greater than 2-1/4” in height and 4” in width.

Washing & Drying Guidelines:

backing type	wash / dry type			
	industrial*	commercial	dry clean	home**
low-melt glue	sew on	sew on	sew on / heat seal	sew on / heat seal
Velcro®	no	no	caution	caution
pressure sensitive “stick-on”	no	no	no	no
non-woven material (no glue)	sew on	sew on	sew on	sew on

*It is recommended not to expose heat sealed emblems to wash or drying conditions exceeding 200°F (93°C).

**Emblems with accessory attachment options should be exposed to hand washing only.

Ordering Guidelines

Artwork & Set-up Fees:

No fees*. There are no artwork or set-up fees when existing, electronic or physical designs or samples are provided. Artwork fees may apply when designs are created from scratch.

Order Quantities:

Minimum 25. The minimum order quantity is 25 pieces, including emblems with Velcro® or pressure sensitive “stick-on” backings, and emblems with accessory options.

Pre-production Samples:

Available \$. Pre-production samples are available for approved designs. Samples fees may apply relative to design detail and emblem size. See price guide for more information.

Pricing:

Charted & quoted. Charted pricing is available up to a certain size threshold, with larger quantities and larger emblem sizes custom quoted. See price guide for more information.

Delivery Times:


Delivery times are relative to order quantity and accessory options if chosen. See price guide for more information.

Ordering Guidelines:

Order specifics. During the design, artwork and ordering processes, there are specific details that we require in order to proceed with your request, such as:

- Emblem Type • Design Colours • Fabric Colour • Border Colour • Dimensions • Backing Type • Quantity • Special Delivery Needs

Emblem sizes are calculated by adding the height (h) and the width (w), then dividing by two. Example 2” (h) + 4” (w) = 6 divided by 2 = 3.



Accepted Design / Artwork File Types:

The chart below lists the various graphic and design file types that Emblemtek will accept for artwork and production purposes. Certain file types are preferred as noted.

Graphic File Types:

- CorelDraw ver.13 / ver.X3 (.cdr) **pref**
- Adobe Illustrator ver.CS3 (.ai) **pref**
- Encapsulated PostScript (.eps) **pref**
- Adobe Portable Document File (.pdf) **pref**
- Joint Photographic Experts Group (.jpg) **pref**
- Portable Network Graphics (.png) **pref**
- Adobe Photoshop ver.CS3 (.psd)
- Corel Photo-Paint ver.13 / ver.X3 (.cpt)
- Targa Bitmap (.tga)
- Tagged Image File Format (.tiff)
- Windows Bitmap (.bmp)
- CompuServe Bitmap (.gif)

Embroidery File Types:

- Tajima Stitch File (.dst) **pref**
- Wilcom EMB File (.emb) **pref**
- Pulse Embroidery File (.pxf)
- Tajima TBF File (.tbf)
- Barudan Stitch File (.dsb)
- Melco Expanded File (.exp)

Emblemtek is pleased to offer you service in English or French, Canada's official languages. Emblemtek trademarks, logos, designs and trade forms may not be used, copied or reproduced without express written consent. The details contained within this document are offered for informational purposes only. These details are subject to change without advanced notice. No liability should be drawn from errors or omissions with respect to this information. It is the responsibility of the purchaser to be aware of Emblemtek's policies in full.

Madeira Polyneon™ is a trademark of Madeira KG.

Teflon® is a registered trademark of E. I. du Pont de Nemours

Velcro® is a registered trademark of Velcro Industries B.V.

TekSpec™ is a trademark of Emblemtek Solutions Group Inc.

© copyright 2011, Emblemtek Solutions Group Inc.